



FLD-12




FLD-12-GRN



FLD-12-WH

DIMENSIONS:



FLD-12 6-5/8"(L) x 4-7/8"(H) x 4"(D)
 FLD-30 7-3/4"(L) x 5-3/4"(H) x 5-1/8"(D)



Mounts to landscape post or any 1/2" hub



Easily mounts to 1/2" hub on weatherproof box



Isolated driver compartment



Fully adjustable 1/2" threaded knuckle for aiming versatility

Bullet LED Flood Light

Ideal for general site lighting, landscape, sign lighting, flag poles and pathways. Driver located in isolated compartment for improved thermal management.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120/277V AC
- Wattage: 12W
- Other wattages available: 30W
- Power factor: >0.9

LIGHTING SPECIFICATIONS:

- LED type/brand: CREE
- Total lumens: CW 850 WW 800
- Color temperature: CW 5000K/ WW 3500K
- Color rendering index: >72
- Beam angle: 90°

SPECIAL FEATURES:

- Total versatility provided by fully adjustable 1/2" threaded knuckle

HOUSING SPECIFICATIONS:

- Die-cast aluminum with powder coat finish
- Tempered glass lens with seamless silicone gasket
- Fluted reflector provides even light distribution
- Suitable for wet locations, IP54
- Color Available: White, Dark bronze, Green

MOUNTING:

- Can be mounted on a round cover or landscape spike with 3" PVC cap

WARRANTY: 7 years

CERTIFICATIONS: UL/cUL, DLC for 5000k and 3000k models

MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
FLD-12CW	12W	120/277V AC	850	5000K
FLD-12WW	12W	120/277V AC	800	3500K
FLD-12CW-WH	12W	120/277V AC	850	5000K
FLD-12WW-WH	12W	120/277V AC	800	3500K
FLD-12CW-GRN	12W	120/277V AC	850	5000K
FLD-12WW-GRN	12W	120/277V AC	800	3500K

