




## DIMENSIONS:



H 5" x W 5" x D 2"



Recessed Mounting



Surface Mounting

## LED Disc Downlight 4"

Universal surface mount  
 Fits most J-boxes & 5"/6" recessed housings  
 New direct A/C technology does not require an LED driver,  
 contributes to longer life and generates less heat.  
 Rated for wet location.  
 Saves up to \$452.22  
 Last up to 30 years

### ELECTRICAL SPECIFICATIONS:

- Working voltage: 120V AC
- Watts: 9W
- CRI: 90
- Power factor: 90% +

### LIGHTING SPECIFICATIONS:

- Fully dimmable
- Lumens: 600
- Beam angle: 120°
- LED: Epistar —35,000 hour design life
- Lens: Translucent acrylic
- Color temperature: 2700K and 3000K (Warm white) ,  
 4100K (natural white), 5000K Daylight

**CERTIFICATIONS:** UL listed, Energy Star-rated

DIAMETER	WATTS	VOLTAGE	LUMENS	COLOR TEMP
4"	9W	120V AC	550~600	WW 2700K
4"	9W	120V AC	550~600	WW 3000K
4"	9W	120V AC	550~600	NW 4100K
4"	9W	120V AC	550~600	DL 5000K

### HOUSING SPECIFICATIONS:

- Finish: White powder coat
- Housing: Spun aluminum
- Trim ring: Integrated spun aluminum white powder coat finish
- Gasket: Neoprene foam gasket
- Suitable for damp locations
- Maximum ambient 4°C (104°F)
- Suitable for use in IC Rated recessed housings

