

JOB NAME: _____

DATE: _____

TYPE: _____



Accessories:



Includes medium base E-26 screw-in adaptor that fits any standard incandescent downlight



Quick connect for easy installation



GU24 Adaptor that fits any GU24 socket



Molex male adaptor optional

RDL6-27K-WP / RDL6-30K-WP RDL6-35K-WP / RDL6-41K-WP RDL6-50K-WP / RDL6-65K-WP

LED Trims

Isolated driver for improved thermal management

ELECTRICAL SPECIFICATIONS:

- Voltage: 120V AC
- Wattage: 19W
- Power factor: 90% +

LIGHTING SPECIFICATIONS:

- LED type/brand: EPISTAR chip (COB) and Driver-35,000-hour design life
- Dimmable: Yes
- Color temperature: Warm white: 2700K, 3000K, 3500K 4100K(Natural white), Daylight: 5000K, 6500K
- CRI: 90

OTHERS:

- Net weight: 0.76lbs / 345g
- Gross weight per CTN: 43.65lbs / 19.8kg

CERTIFICATIONS:

- UL listed
- Energy Star-rated (2700K, 3000K, 4000K, 5000K)

MODEL NO	WATTAGE	LUMENS	VOLTAGE	COLOR TEMP
RDL6-27K-WP	19W	1200	120V AC	WW 2700K
RDL6-30K-WP	19W	1250	120V AC	WW 3000K
RDL6-35K-WP	19W	1275	120V AC	WW3500K
RDL6-41K-WP	19W	1300	120V AC	NW 4100K
RDL6-50K-WP	19W	1350	120V AC	DL 5000K
RDL6-65K-WP	19W	1400	120V AC	DL 6500K

HOUSING SPECIFICATIONS:

- Housing: Spun aluminum with white powder coat finish
- Trim ring: Integrated spun aluminum white powder coat finish
- Gasket: Close cell Neoprene foam gasket
- Lens: 0.125" white translucent acrylic
- Wet locations: Suitable for damp locations
- Maximum ambient 4°C (104°F)

WARRANTY:

- Five-year warranty

