




DIMENSIONS:



2" H x 7.5" W x 7.5" D



Recessed Mounting



Surface Mounting

LED Disc Downlight 6"

Universal surface mount
 Fits most J-boxes & 5"/6" recessed housings
 New direct A/C technology does not require an LED driver,
 contributes to longer life and generates less heat.
 Rated for wet location.
 Saves up to \$452.22
 Last up to 30 years

ELECTRICAL SPECIFICATIONS:

- Working voltage: 120V AC
- Watts: 15W
- CRI: 90
- Power factor: 90% +

LIGHTING SPECIFICATIONS:

- Fully dimmable
- Lumens: 1000
- Beam angle: 120°
- LED: Epistar —35,000 hour design life
- Lens: Translucent acrylic
- Color temperature: 2700K and 3000K (Warm white), 4100K (natural white), 5000K Daylight

CERTIFICATIONS: UL listed, Energy Star-rated

DIAMETER	WATTS	VOLTAGE	LUMENS	COLOR TEMP
6"	15W	120V AC	950~1000	WW 2700K
6"	15W	120V AC	950~1000	WW 3000K
6"	15W	120V AC	950~1000	NW 4100K
6"	15W	120V AC	950~1000	DL 5000K

HOUSING SPECIFICATIONS:

- Finish: White powder coat
- Housing: Spun aluminum
- Trim ring: Integrated spun aluminum white powder coat finish
- Gasket: close cell Neoprene foam gasket
- Fits 6" housings
- Works with most dimmers
- Suitable for damp locations
- Maximum ambient 4°C (104°F)

