

JOB NAME: \_\_\_\_\_

DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_



### Accessories:



Includes medium base E-26 screw-in adaptor that fits any standard incandescent downlight



Quick connect for easy installation



GU24 Adaptor that fits any GU24 socket



Molex male adaptor optional

## RDL4-BF-27K / RDL4-BF-30K RDL4-BF-41K / RDL4-BF-50K

### LED Trims 4"

Isolated driver for improved thermal management.

#### ELECTRICAL SPECIFICATIONS:

- Voltage: 120V 50/60Hz
- Wattage: 11W
- Power factor: 90% +
- Replacement: 75w

#### LIGHTING SPECIFICATIONS:

- Base: E26/ GU10/ GU24
- CRI: ≥90ra
- Color temperature: 2700K and 3000K (Warm white), 4100K(Natural white), 5000K (Daylight)
- Beam angle: 90°

#### SIZE:

- Product size: 128\*60mm
- Hole size: 110mm
- Gross weight per pcs: 233kg

#### WARRANTY:

- Five-year warranty

MODEL NO	WATTAGE	LUMENS	COLOR TEMP
RDL4-BF-27K	11W	650	WW 2700K
RDL4-BF-30K	11W	700	WW 3000K
RDL4-BF-41K	11W	750	NW 4100K
RDL4-BF-50K	11W	800	DL 5000K

#### HOUSING SPECIFICATIONS:

- Housing: Spun aluminum with white powder coat finish
- Trim ring: Integrated spun aluminum white powder coat finish
- Gasket: Close cell Neoprene foam gasket
- Lens: 0.125" white translucent acrylic
- Maximum ambient 4 °C (104 °F)

#### CERTIFICATIONS:

- UL listed
- Energy Star-rated (2700K/3000K and 4000K)
- ETL

