

Project

Schedule / Date

Notes

Catalog Number

DAL

### Product Description

naturalLED® Decorative Accent fixtures feature a soft white light, created by a diffused acrylic lens, and a nickel finished trim. This dimmable fixture has 50,000 hours average rated life, is available in a 24" size, and may be mounted horizontally or vertically.

Our Decorator Accent fixture can be in used in residential, commercial, hospitality, office buildings and many other applications, making it a perfect energy saving and low maintenance LED solution.



### Features & Benefits

- ▶ Energy Star Certified
- ▶ Damp Rated
- ▶ Lightweight for easy installation
- ▶ Excellent thermal design
- ▶ Uniform and consistent color
- ▶ Long Life LED chips
- ▶ UL Listed
- ▶ Rated 50,000 hours average life
- ▶ UV Coated Frosted Polycarbonate
- ▶ Finish: Nickel

### Specifications

- ▶ Input line voltage: 120V
- ▶ Dimmable
- ▶ Operating temperature: -22°F ~ 122°F
- ▶ Available in 24-inch configurations

### Applications

- ▶ Bathroom Lighting
- ▶ Over Mirror Lighting
- ▶ Hotel Bathroom Lighting
- ▶ Furniture Top Lighting
- ▶ Make-up Mirror Lighting




Ordering Information

Code	Description	CCT	Watt	Lumen	Equiv Wattage	Size	Beam Angle	Dim	Rated Hrs	DAMP LOCATION	ENERGY STAR
7020	LED-FXDAL23/24FR/830/NI	3000K	23	2,000	200	24-inch	Flood	Yes	50,000	•	•
7021	LED-FXDAL23/24FR/840/NI	4000K	23	2,000	200	24-inch	Flood	Yes	50,000	•	•

Photometric Data

FXDAL23 / 24"



Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	65.00	2.50
0-40	160.11	6.30
0-60	520.01	20.40
60-80	560.19	22.00
70-80	299.36	11.70
90-120	794.96	31.20
90-180	1153.34	45.20
0-180	2551.81	100.00

Total Luminaire Efficiency = 100.00%

Distance	Illuminance at a Distance	
	Center Beam fc	Beam Width
5.0ft	0.09 fc	11.8 ft 47.2 ft
10.0ft	0.02 fc	23.5 ft 94.4 ft
15.0ft	0.01 fc	35.3 ft 141.6 ft
20.0ft	0.01 fc	47.0 ft 188.9 ft
25.0ft	0.00 fc	58.8 ft 236.1 ft
30.0ft	0.00 fc	70.6 ft 283.3 ft

■ Vert. Spread: 99.3°  
■ Horiz. Spread: 156.1°

Product Dimension

24-inch

Weight: 4.41-lbs

