

Project:	
Part#:	
Туре:	



Applications:

- · General outdoor lighting
- Landscape lighting
- Pathways, streets, loading areas, etc.

Detail Specifications

- IC DOB Chip with 50,000 hour life span
- Operating temperature -4 -- + 104 F°
- PF >0.9 / Input: .85A/ Output: 36-66V DC

LED Cusp Disk Light Surface Mounts

The EnVision AC Cusp disk can be used in new construction and remodel applications. EnVisions new disk uses AC technology, features a slim aluminum body, with a transluscent diffuser for reduced glare. EnVisions disk can be mounted into a 30 or 40 j-box giving it versatility and is a great solution that offers energy efficienct and streamline design.

Product Information:

- Sturdy die-cast aluminum housing finished with corrossion free powder coat
- Damp rated or wet rated (with silicone)
- Fits in standard 3O or 4O J-Box applications
- Driver: AC Driverless technology 120V

- High CRI >90 with CA Title 24/ CEC/ T20 Compliance
- Dimmable: Compatible with most dimmers down to 5% including Lutron DVCL-153P

L E D - C	<i>D S K</i> -	Size _	Watts _	Color 4	_ Finis	sh <u> </u>	
1 Product LED-CDSK Cusp Disk Light 2 Size 3 Watts		4 Color	5 Finis	5 Finish		6 Emergency	
4 4" (4.4" Width)	10W 10W 600lm	27K 2700k 30K 3000k 40K 4000k	BZ	White Bronze Brushed Nickel	(blank)	n/a Emergency Backup	
6 6" (7.4" Width)	15W 15W 1000lm	50K 5000k	Brushed N only avai Other option	Brushed Nickel and Bronze only available in 6" 3000k. Other options custom/ will be added at a later date		, , , ,	
8 8" (9.4" Width)	18W 18W 1400lm	30K 3000k 40K 4000k					









LED CUSP DISK SERIES

APPLICATIONS







30 Round (plastic) J-Box

All Cusp Disk feature a

slim 1" Width



30 Square (plastic) J-Box



40 Round (metal) J-Box



40 Square (metal) J-Box

Diva

Diva

Maestro

Rotary

Electronic(ELV)

Skylark

Skylark Contoui

Skylark Contour

Toggler

Toggler

Sureslide

Trimatron

ILLVMATECH

Adorne

Harmony

Aspire

Maestro Wireless



40 Square (fire rated) J-Box

DIMMER COMPATIBILITY

AYCL-153P

DV-600PR

DVCL-153P

MACL-153MH

MRF2-6CL

D-600P

NTELV-300P

S-600P

CT-600P

CTCL-153P

TG-600P

TGCL-153P

6633

6674

6602

IPL06

ADTP703TU

H703PTW

9540

DAL06P

150W

600W

150W

600W

600W

600W

600W

600W

150W

600W

150W

600W

600W

600W

600W

700W

700W

1000W

300W

ОК

ОК

ОК

OK

ОК

OK

ОК

OK

ОК

ОК

OK

20-100%

20-100%

ОК


20-100%

ОК


ОК

ОК

DIMENSIONS



6" Disk (7.4" Width)



8" Disk (9.4" Width)

FEATURES



Driverless AC technology

High Quality Lens

allows for a unique and **Reliable LED Chips** PMMA Lens to ensure slim low profice design no cracking, yellowing, Philips 3030 LED chips for or lumen deficiency longevity, consistent color, and reliability Waterproofing **Driverless**

Plastic lens creates IP65 waterproofing. Make your fixture IP67 by adding silicone around the lens

Heat Dissipation

Made out of thick aluminum di-cast to withstand harsh conditions and disspate heat

Slim profile without a driver sticking in the back allows for universal installation