


LED Flexible Strip



Description

The 6474-IP67-Sauna is engineered for high-temperature environments, making it ideal for hot outdoor patios, saunas, and beaches. While standard LED strips might melt or fail, this strip is designed to withstand extreme heat, ensuring reliable, high-quality illumination in challenging settings.

Input Voltage	24V DC
Limiting Control method	Constant voltage
Power consumption	3 W/FT
Beam Angle	120°
Reel Length	16.4 ft (5m) / 49.2 ft (15m)
Segment Width	0.4 in(10mm)
Luminous Flux Maintenance	75,000 hrs
Dimming	DMX PWM, RF PWM, 0-10V, MLV, Incandescent
Warranty	3 Years Limited
Certifications	 UL Listed, E467088
Operating Temperature	-20°F to 217°F
Mounting	Mounting clips
LED Chip type	High quality COB
Led density	146LEDs/ft / 480LEDs/m
Board type	3OZ, White PCB
Max run	16.4ft/5m

Nominal CCT (K)	Luminous Flux (lm/ft)	Luminous Efficacy (lm/W)	CRI
2700K	267	89	90+
3000K	270	90	90+
4000K	275	92	90+
6000K	289	96	90+



Ordering Guide

Series	CCT	Voltage	IP Rating
6474	XX	XX	XX

1 - Contact Richee for exact warranty period and policy.

2 - Lumen output are measured according to PMS-80, with a tolerance of +/- 5%.

3 - Standard package: 5m/roll, 15m/roll, 30m/roll.