

## Wall Pack Full Cutoff 5 Power + 3CCT Switchable

Light up your outdoor area with the EnVision Bolt Series, a line of outdoor fixtures with high lumen per watt efficacy. The Bolt Wall Packs are available in a variety of different styles: non-cutoff, fully cut-off, semi cut-off, adjustable, and a rotatable up/down light. EnVision's full cut off wall pack is industry leading with a slim architectural design that features an optic lens that provides forward-throw light.

### Applications:

- General outdoor lighting
- Landscape lighting
- Pathways, streets, loading areas, etc.

### Product Information:

- Photocell included (Easily disconnectable)
- Sturdy die-cast aluminum housing finished with corrosion free powder coat
- Suitable for wet location, professionally waterproofed IP67
- Average life (L70) of 70,000 hours with the integration of Philips Lumileds 3030 chips
- Dark sky compliant

### Detail Specifications:

#### 5P60

- Operating temperature -4 -- + 124° F
- PF >0.9 / Input: .55A/ Output: 100-144V DC
- 120-277V / 0-10V LED Dimmer

#### 5P120

- Operating temperature -4 -- + 124° F
- PF >0.9 / Input: 1.15A/ Output: 70-94V DC
- 120-277V / 0-10V LED Dimmer

### Why pick the Envision Wall Pack?:

- Each wall pack is tested for 120 hours before being packed and shipped
- Optic lens provides forward throw light
- Easy installation with twistable screw knock-outs
- 5 year limited warranty. 10 year warranty available



LED	WPFC	FL	5-Power Selectable	TRI	Finish	PC	Voltage	Access.	Options	Warranty
1	2	3	4	5	6	7	8			

1 Product	2 5-Power Selectable	3 Color	4 Finish	5 Voltage	6 Accessories	7 Options	8 Warranty
LED-WPFC-FL	<b>5P60</b> 20/30/40/50/60W 2,900lm (20W) / 4,350lm (30W) 5,800lm (40W) / 7,250 (50W) 8,700 (60W)  <b>5P120</b> 80/90/100/110/120W 11,600lm (80W) / 13,050lm (90W) 14,500lm (100W) / 15,950lm (110W) 17,400lm (120W)	<b>TRI</b> 3CCT Switchable 50/40/30K	<b>BZ</b> Bronze <b>Custom</b> Custom* <i>*Custom colors available. 7-10 day lead time, colors include white, black, etc.</i>	<b>UNV</b> Universal <b>HV</b> 347-480V Step Down Transformer	<b>(Blank)</b> None <b>PC</b> Photocell <b>BMS</b> Bi-Level Motion Sensor <b>BT</b> Bluetooth	<b>(Blank)</b> None <b>EMB</b> Emergency Backup (90 Mins.)	<b>(Blank)</b> 5 Year (incl. 10YR) 10 Year

Specs and model numbers are subject to change with or without notice.

**DIMENSIONS****FEATURES**

Waterproof Gasket

Easy Open

Photocell

Efficient Lighting

Light Dispersion

