



## SINGLE COLOR WHITE FLEXIBLE LIGHT SHEET

BACKLIGHTING // FLEXIBLE LIGHT SHEETS // AURAGAMI

PART #: AG2-24-XX-1224 | XX = 2700K, 3000K, 3500K, 4000K, 5000K

**Product Description:** Auragami Gen 2 Single Color White is the most advanced light sheet ever created. It features revolutionary improvements over the original award-winning AG1 series.

### HIGHLIGHTS

- Available in five single color white temperatures
- New and improved IP67 connectors, cut lines, and bumpers
- IP67 Rated for wet locations with newly engineered polyimide coating
- Cuttable down to a single LED or LED group while maintaining UL Listing
- Easy installs with plug-in-play light sheet connections
- Patented design exemplifies ingenuity and advantage



### ELECTRICAL


Input Voltage	24VDC - Constant Voltage
Power Consumption	17.2W per sheet (8.6W/ft <sup>2</sup> , 93W/m <sup>2</sup> ); 0.034W per LED
Wires	20AWG 2 wire (grey striped wire +, white wire -)
Connections	IP67 premium grade terminals and plug-in sheet connectors
Certifications	UL Listed (E495221), CE Compliant (EMC and LVD), RoHS Certified, UKCA

### PHYSICAL

Color Temperature	2700K, 3000K, 3500K, 4000K, 5000K
CRI	92+ for 2700K, 95+ for 3000K, 3500K, 4000K, 5000K
Light Output	1720 lumens per sheet
Mounting	Use mechanical fasteners through marked mounting holes. Adhesive backing is a supplementary method.
Operating / Working Temperature	<b>Operating:</b> -22°F to 122°F (-30°C to 50°C), <b>Working:</b> 93°F (34°C),
Surface Temperature	<b>LED:</b> 97°F (36°C), <b>PCB:</b> 90°F (32°C), <b>Resistor:</b> 93°F (34°C) (Measurements taken at ≥ 2 hours of operation)
Environment	IP67 - wet and dry locations
Coverage	2ft <sup>2</sup> (0.19m <sup>2</sup> ) per sheet / up to 10ft <sup>2</sup> (0.93m <sup>2</sup> ) per Class 2 guidelines
Cut/Fold Line Spacing	0.75" (19.5mm) short axis / 0.75" (19.5 mm) long axis
Dimensions	12" x 24" (304.8mm x 609.6mm), field cuttable
Weight	0.65lbs / 10.4oz / 295g

### PRODUCT CONTENTS

Each Auragami Gen 2 Light Sheet comes standard with the following items:



### FEATURES

Field Customizable	Maintains UL Listing when cut
Full Integration Support	From concept to completion
Unique Power Distribution Grid	Groups or single LEDs can be cut from anywhere on light sheet
Flexible / Foldable PCB	Polyimide film substrate
Consistent Light Quality	Tight ANSI bin control LEDs
LED Quantity / Density	512 SMD type 2835 LEDs per sheet
Energy Efficiency	100 lumens per watt
Long Lifespan	50,000+ hours
Advanced 5-Year Warranty	Visit section 19 of <a href="http://evo-lite.com/legal-documents#terms">evo-lite.com/legal-documents#terms</a>

### POWER & CONTROLS

Compatible with all control protocols via associated power and control components. Quality tested for low-end light output consistency across all LEDs (100-0%).

### CLASS 2 & UL COMPLIANCE


Use Class 2 power supplies with a maximum power output of 96W (per channel/circuit) to retain UL Class 2 Listing compliance. Best practices include allowing headroom for power supply longevity.

### COMPLETE YOUR SYSTEM (SOLD SEPARATELY)


Don't forget to order the appropriate lighting system components.




AG2 SINGLE COLOR WHITE LIGHT SHEET (INCLUDED)



LIGHT SHEET & LED HEIGHT




IP67 TERMINAL DIMENSIONS




ACCESSORY PACK (INCLUDED)

Short Sheet To Sheet Connector (Qty. 2)




Long Sheet To Sheet Connector (Qty. 2)




BUMPER PACK (SOLD SEPARATELY)

Quad Bumpers (Qty. 8)




POWER INPUT KIT (SOLD SEPARATELY)


Power Input Cable (Qty. 1)



Cable Clips (Qty. 4)



Wago Connectors (Qty. 2)




## ORDERING INFORMATION

### SINGLE COLOR WHITE LIGHT SHEETS (Customization options available, see bottom of page.)

MODEL	VOLTAGE	COLOR TEMPERATURE	SHEET SIZE
AG2 - Auragami Gen 2	24 - 24VDC Constant Voltage	27 - 2700K	1224 - 12" by 24"
		30 - 3000K	
		35 - 3500K	
		40 - 4000K	
		50 - 5000K	

#### Example Part Number



### SINGLE COLOR ACCESSORIES (SOLD SEPARATELY)

ITEM	PART NUMBER	DESCRIPTION
Single Color Power Input Kit <i>(Required)</i>	AG2-SC-PIK	Powers one 24VDC Class 2 circuit (86W / 5 full light sheets). Includes (1) 48" single color power input cable, (2) Wago splicing connectors, and (4) wire management clips.
Short Sheet To Sheet Connectors	AG2-24-SC-SCP	(4) Additional Single Color Short Sheet To Sheet Connectors.
Long Sheet To Sheet Connectors	AG2-24-SC-LCP	(4) Additional Single Color long Sheet To Sheet Connectors.
Light Sheet Bumpers	AG2-075-047-QSB-P08	(8) Additional Light Sheet Quad Bumpers for single color and tunable white light sheets.
Auragami Installation Roller	AG1-RLR-EVO	Specially designed foam roller assists in light sheet mounting. Safely mount light sheets without damaging terminals or LEDs.
Electronic Grade Silicone	SI-388CL-EVO	Acid-free electronic grade silicone may be used to supplement cut edges and connection terminals


### SUGGESTED POWER OPTIONS (We stock a variety of the most popular power supplies (not shown below). Let us know if you have a preference.)

ITEM	PART NUMBER	DESCRIPTION
24V, 5-IN-1 Dimmable LED Driver (1 circuit of 96W)	PS-5N1-1C2496-EVO	24VDC 5-IN-1 Dimmable LED Driver. Compatible with most control protocols: Triac / Phase, 0-10V, 1-10V, Potentiometer, and 10V PWM. 1 circuit of 96W.
24V, 5-IN-1 Dimmable LED Driver (2 circuits of 96W each)	PS-5N1-2C24192-EVO	24VDC 5-IN-1 Dimmable LED Driver. Compatible with most control protocols: Triac / Phase, 0-10V, 1-10V, Potentiometer, and 10V PWM. 2 circuits of 96W each.
24V, 5-IN-1 Dimmable LED Driver (4 circuits of 96W each)	PS-5N1-4C24384-EVO	24VDC 5-IN-1 Dimmable LED Driver. Compatible with most control protocols: Triac / Phase, 0-10V, 1-10V, Potentiometer, and 10V PWM. 4 circuits of 96W each.

### SUGGESTED CONTROL OPTIONS


We stock and offer the most popular lighting control types and brands including, Leviton, LTECH, Sunricher, AmbienTech, Dali, DMX, and more. Please let your System Integration Specialist know if you have a control type preference or would like a suggestion. Auragami is compatible with all control types via associated control components.

## ALSO AVAILABLE FROM EVO-LITE




#### TUNABLE WHITE

Adjustable white from warm 1800K to cool 6500K



#### RGB + 5000K WHITE

Billions of colors + dedicated 5000K white diodes.



#### AURAGAMI BASIC

2700K, 3000K, 3500K, 4000K, 5000K, TW, RGBW

#### CUSTOMIZATION OPTIONS

All Auragami customizations maintain the UL Listing. Minimum order quantities apply.

- Voltage
- Wattage/efficiency
- Lumens/brightness
- Specific color temperatures
- IP Ratings
- Pre cut sheets with factory sealed IP Rating
- LED pitch and placement
- PCB material type, pre-cut sheets
- Pre-mounted to quick install substrates

This product comes with an advanced 5-year warranty. Please review section 19 of Terms & Conditions of Sale at [evo-lite.com/legal-documents#terms](http://evo-lite.com/legal-documents#terms)  
 Auragami® is a patented product of Evo-Lite, LLC. For more information please visit [www.evo-lite.com/patent](http://www.evo-lite.com/patent)