



UPC Code : 078477704851

Country Of Origin : Mexico



## 16352-1PW

Decora Plus Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Split-Circuit, One Outlet Marked "Controlled", Smooth Face, 20 Amp, 125 Volt, Back or Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - White

Leviton offers custom imprinting solutions to meet the 2014 National Electrical Code requirements for identifying receptacles that will be automatically de-energized as part of an overall plug load control program. All 15A & 20A, 125V receptacles that are automatically controlled will be marked with a specific symbol.

### Technical Information

#### AC Horsepower Ratings

**At Rated Voltage** : 1 HP

#### Electrical Specifications

**Amperage** : 20 A

**Current Limiting** : Full Rated Current

**Dielectric Voltage** : Withstands 3000V per UL498

**Grounding** : Self-Grounding

**Pole** : 2

**Temperature Rise** : Max 30C temperature rise at full rated current

**Voltage** : 125 VAC

**Wire** : 3

#### Environmental Specifications

**Flammability** : Rated V-2 per UL 94

**Operating Temperature** : -40°C to 75°C

#### Material Specifications

**Body Material** : PBT Polyester Blend

**Clamp Nuts** : Steel

**Color** : White

**Face Material** : PBT Polyester Blend

**Ground Clips** : Brass

**Grounding Screw** : #8 Hex Head, Triple-Drive Brass

**Line Contacts** : .030" Brass

**Strap Material** : Steel (Galvanized G60)

**Terminal Screws** : #8 Triple Drive Brass

#### Mechanical Specifications

**Product ID** : Ratings are permanently marked on device

**Terminal Accom.** : 14-10 AWG

**Terminal ID** : Brass-Hot, Green-Ground, Silver-Neutral

**Termination** : Back and Side Wire

#### Product Features

**Brand** : Decora Plus

**Color** : White

**Device Type** : Duplex Receptacle Outlet

**Feature** : Split-circuit, One Outlet Marked Controlled

**Feature 4** : Smooth Face

**Grade** : Heavy-Duty Industrial Specification Grade

**Grounding** : Self-Grounding

**NEMA** : 5-20R

#### Standards and Certifications

**ANSI** : C-73

**NEMA** : WD-1 & WD-6

**Warranty** : 10-Year Limited

### Patents\*

CA2483480


US6743029

MX257790

US8684771

MX321216

\*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.



Drawing Applies to 15 & 20A Devices

### SPECIFICATION SUBMITTAL

JOB NAME:		CATALOG NUMBERS:	
<input type="text"/>		<input type="text"/>	<input type="text"/>
JOB NUMBER:		<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

