

# Thermoplastic LED Emergency Combo



## FEATURES:

- Energy efficient LED compact and decorative design.
- Removable directional indicators, letters.
- 6" height with 3/4" stroke and chevron directional arrows.
- Double or single face universal pack.
- 90+ minutes emergency operation.
- Available in white or black housing.

**LS26-CEX**



## MOUNTING:

- Universal (wall, side or ceiling) mounting.
- Universal knockouts on back plate allow for wall mounting directly to standard J-Box.
- Canopy and mounting hardware provided.

## ELECTRICAL:


- 120/277V dual voltage operation standard.

## LAMPS:

- 3 Watts LED at 120V and 277V, LED lamps are operating in normal (AC input) and Emergency (DC input) modes.
- Ultra-bright, energy efficient, long-life Red or Green LEDs with more than 10 years lifecycle.
- LEDs have a minimum rated lamp life of 100,000 hours.

## BATTERY:

- 3.6V long-life maintenance-free and rechargeable Ni-Cad battery on emergency (EM) units.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Internal solid-state transfer switch automatically connects the internal battery to LEDs for minimum 90minute emergency illumination
- LVD (Low Voltage Disconnection) prevents battery from deep discharge.



## LISTING:

- 5 years limited warranty on materials and all electronics. Battery is pro-rated for five years.
- LED lamps are 25 years limited warranty.
- UL listed for damp locations. (32°F ~ 104°F / 0°C ~ 40°C)
- Meets UL924, NFPA 70, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

## ORDER INFORMATION

Model	Voltage	Color	Emergency Duration	Certificate
LS26-CEX-R	120/277V	Red	90 minutes	UL
LS26-CEX-G	120/277V	Green	90 minutes	UL