


Project Name:	Notes:	Date:	Type:
---------------	--------	-------	-------

### DESCRIPTION

Portor's TC3 is wattage and color tunable, and can be programmed with a CCT of 3500K, 4000K, or 5000K, eliminating the need to stock multiple color temperatures.

Ideal use for office spaces , walkways, schools/campuses, shopping centers, hospitality and health care industry.



### CONSTRUCTION

Constructed of one-piece ribbed unitized housing and corners that interlock, preventing damage to luminaire. All sides and corners are turned in and hemmed, removing sharp edges for safe handling and installation.

### ELECTRICAL

Luminaire is built with the highest quality 100-277VAC drivers.

### OPTICAL SYSTEM

Designed to reduce glare and improve light distribution through precision formed lens optics.

### DIMMING

0-10V dimmable standard

### LISTING

DLC Premium Listed , UL Listed, FCC, RoHS, IP44 Rated

### TECHNICAL SPECIFICATION

WATTAGE	30W/35W/40W
LUMENS	up to 5,000 lumens
EFFICACY	125 lm/W
CURRENT	0.367A
VOLTAGE	AC100-277V
POWER FREQUENCY	50/60 Hz
CCT	3500K/4000K/5000K
CRI	Ra>80
BEAM ANGLE	120°
WORKING TEMP.	-40°F - +122°F
STORAGE TEMP.	-40°F - +158°F
IP RATING	IP44 Suitable for damp locations
DIMMABLE	0-10V dimming
POWER FACTOR	>0.9
THD	≤20%
WARRANTY	5 year limited





### MODEL NUMBER(S)

MODEL#	WATTS	LUMENS	LM/WATT	CCT	CRI	VOLTAGE
PT-TC3-24-3CP	30W/35W/40W	up to 5,000	125	3500K/4000K/5000K	>80	AC 100/277V

Project Name:	Notes:	Date:	Type:
---------------	--------	-------	-------

### DIMENSION



### OPTIONS



**EMERGENCY BATTERY BACK-UP**  
(Inquire factory for more info)



**PT-A-MSS-TR**  
Microwave Bi-Level Motion Sensor  
for Troffer

### PHOTOMETRY

