



750W Slim Type with PFC Switching Supply

UHP-750 series



User's Manual



Video



■ Features

- Slim and Low profile (41mm)
- Fanless and conduction-cooled design
- Withstand 300VAC surge input for 5 seconds
- Built-in active PFC function
- -30~+70°C working temperature
- Protections: Short circuit / Overload / Over voltage / Over temperature
- DC OK relay contact
- Operating altitude up to 5000 meter (Note.6)
- LED indicator for power on
- 3 years warranty

■ Applications

- Industrial automation machinery
- Industrial control system
- Mechanical and electrical equipment
- Electronic instruments, equipment or apparatus
- Household appliances
- Power Sourcing Equipment of PoE (48V model: DC O/P range 48~57.6V)

■ GTIN CODE


MW Search: <https://www.meanwell.com/serviceGTIN.aspx>

■ Description

UHP-750 series is a 750W single-output slim type power supply with 41 mm of low profile design. Adopting the full range 90~264VAC input, the entire series provides an output voltage line of 12V, 24V, 36V and 48V. In addition to the high efficiency up to 95%, that the whole series operates from -30°C ~ 70°C under air convection without fan. UHP-750 has the complete protection functions and 5G anti-vibration capability; It is complied with the international safety regulations such as TUV BS EN/EN62368-1 and UL62368-1. UHP-750 series serves as a high performance power supply solution for various industrial applications.

■ Model Encoding

UHP - 750 - 12






750W Slim Type with PFC Switching Supply

UHP-750 series


SPECIFICATION

MODEL		UHP-750-12		UHP-750-24		UHP-750-36		UHP-750-48			
OUTPUT	DC VOLTAGE	12V		24V		36V		48V			
	RATED CURRENT	60A		31.3A		20.9A		15.7A			
	RATED POWER	720W		751.2W		752.4W		753.6W			
	RIPPLE & NOISE (max.) Note.2	150mVp-p		200mVp-p		250mVp-p		250mVp-p			
	VOLTAGE ADJ. RANGE	12~14.4V		24~28.8V		36~43.2V		48~57.6V			
	VOLTAGE TOLERANCE Note.3	±1.0%		±1.0%		±1.0%		±1.0%			
	LINE REGULATION	±0.5%		±0.5%		±0.5%		±0.5%			
	LOAD REGULATION	±0.5%		±0.5%		±0.5%		±0.5%			
	SETUP, RISE TIME Note.4	1000ms, 50ms/230VAC		1000ms,50ms/115VAC at full load							
	HOLD UP TIME (Typ.)	12ms/230VAC		12ms/115VAC							
INPUT	VOLTAGE RANGE Note.4	90 ~ 264VAC		127 ~ 370VDC							
	FREQUENCY RANGE	47 ~ 63Hz									
	POWER FACTOR (Typ.) Note.4	PF≥0.95/230VAC		PF≥0.98/115VAC at full load							
	EFFICIENCY (Typ.)	93.5%		95%		95%		95%			
	AC CURRENT (Typ.)	7.5A/115VAC		3.8A/230VAC							
	INRUSH CURRENT (Typ.)	Cold start 20A/115VAC		40A/230VAC							
	LEAKAGE CURRENT	<0.75mA / 240VAC									
PROTECTION	OVERLOAD	105~125% rated output power									
		Protection type: Hiccup mode, recovers automatically after fault condition is removed									
	OVER VOLTAGE	14.5 ~ 16V		29 ~ 33V		43.5 ~ 49V		59 ~ 66V			
		Protection type: Shut down O/P voltage, re-power on to recover									
OVER TEMPERATURE	Protection type: Shut down O/P voltage, recovers automatically after temperature goes down										
FUNCTION	DC-OK SIGNAL	Contact rating(max.): 30Vdc/1A resistive load									
ENVIRONMENT	WORKING TEMP.	-30 ~ +70℃ (Refer to "Derating Curve")									
	WORKING HUMIDITY	20 ~ 90% RH non-condensing									
	STORAGE TEMP., HUMIDITY	-40 ~ +85℃, 10 ~ 95% RH non-condensing									
	TEMP. COEFFICIENT	±0.03%/℃ (0 ~ 50℃)									
	VIBRATION	10 ~ 500Hz, 5G 10min./1cycle, 60min. each along X, Y, Z axes									
SAFETY & EMC (Note.5)	SAFETY STANDARDS	UL62368-1,TUV BS EN/EN62368-1, EAC TP TC 004 approved									
	WITHSTAND VOLTAGE	I/P-O/P: 3.75KVAC I/P-FG: 2KVAC O/P-FG: 1.25KVAC									
	ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG: 100M Ohms/500VDC/25℃ / 70%RH									
	EMC EMISSION	Parameter	Standard		Test Level / Note						
		Conducted	BS EN/EN55032 (CISPR32)		Class B						
		Radiated	BS EN/EN55032 (CISPR32)		Class B						
		Harmonic Current	BS EN/EN61000-3-2		Class A						
		Voltage Flicker	BS EN/EN61000-3-3		-----						
	EMC IMMUNITY	BS EN/EN55035, BS EN/EN61000-6-2									
		Parameter	Standard		Test Level / Note						
		ESD	BS EN/EN61000-4-2		Level 3, 8KV air ; Level 2, 4KV contact						
		Radiated	BS EN/EN61000-4-3		Level 3						
		EFT / Burst	BS EN/EN61000-4-4		Level 3						
		Surge	BS EN/EN61000-6-2		2KV/Line-Line 4KV/Line-Earth						
		Conducted	BS EN/EN61000-4-6		Level 3						
		Magnetic Field	BS EN/EN61000-4-8		Level 4						
		Voltage Dips and Interruptions	BS EN/EN61000-4-11		>95% dip 0.5 periods, 30% dip 25 periods, >95% interruptions 250 periods						
OTHERS	MTBF	833.9K hrs min. Telcordia SR-332 (Bellcore); 104.9K hrs min. MIL-HDBK-217F (25℃)									
	DIMENSION	237*100*41mm (L*W*H)									
	PACKING	1.4kg; 10pcs/15kg/0.8CUFT									
NOTE	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25℃ of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance :includes set up tolerance, line regulation and load regulation. 4. Derating may be needed under low input voltages. Please check the derating curve and Static characteristics for more details. 5. The power supply is considered a component which will be installed into a final equipment. All the EMC tests are been executed by mounting the unit on a 360mm*360mm metal plate with 1mm of thickness. The final equipment must be re-confirmed that it still meets EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies." (as available on https://www.meanwell.com/Upload/PDF/EMI_statement_en.pdf) 6. The ambient temperature derating of 3.5℃/1000m with fanless models and of 5℃/1000m with fan models for operating altitude higher than 2000m(6500ft). ※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx										


BLOCK DIAGRAM







STATIC CHARACTERISTIC



EFFICIENCY VS LOAD (48V MODEL)



DERATING CURVE



DC OK RELAY CONTACT


Contact Close	PSU turns on/DC ok
Contact Open	PSU turns off/DC fail
Contact Rating(max.)	30Vdc/1A resistive load

MECHANICAL SPECIFICATION

Case No.270B

Unit:mm

Tolerance:±1



AC Input Terminal(TB1) pin NO. Assignment

Pin No.	Assignment	Terminal	Max mounting torque
1	AC/L	DECA T21-EM10-03	9.2Kgf-cm
2	AC/N		
3	⏏		

DC Output Terminal(TB2, TB3) pin NO. Assignment

Pin No.	Assignment	Terminal	Max mounting torque
1,2	+V	(MW)	8Kgf-cm
3,4	-V	NEL-400-02P	



DC OK Connector(CN11):JST S2B-PH-KL or equivalent

Pin No.	Assignment	Mating Housing	Terminal
1	DC COM1	JST PHR-2 or equivalent	JST SPH-002T-P0.5S or equivalent
2	DC COM2		

Operate with additional aluminum plate and fan

In order to meet the "Derating Curve" and the "Static Characteristics", UHP-750 series can be installed onto an aluminum plate (or the cabinet of the same size) on the bottom or apply forced air cooled solution. The size of the suggested aluminum plate and configuration of fan are shown as below. And for optimizing thermal performance, the aluminum plate must have an even and smooth surface (or coated with thermal grease), and UHP-750 series must be firmly mounted at the center of the aluminum plate.

unit:mm



■ INSTALLATION MANUAL

Please refer to : <http://www.meanwell.com/manual.html>