




# Specification

Model	1732	Range of Application	Outdoor
Photo.		Dimension	Cut size
		Φ 100*H95	Φ 95*H105
Material		Packing Information	
<ol style="list-style-type: none"> <li>304 Stainless steel cover</li> <li>die-casting aluminum body</li> <li>8-10mm step tempered glass</li> <li>plastic casting available</li> <li>sillicon sealed gasket</li> </ol>		<ol style="list-style-type: none"> <li>1 PCS /Inner box</li> <li>30 PCS/Carton</li> <li>N.W:18 KGS , G.W:19.5 KGS</li> <li>Carton size :56*34*25 CM</li> </ol>	
Installation		Light Source Technical Data	
<p>The fitting is suitable to be installed in restricted accessible areas (E. G. pedestrians and pedal cycles only), Rated load if the fitting is 5KN, Rated maximum surface temperature will be 45°C.</p> <ol style="list-style-type: none"> <li>Using the allen key (supplied) remove the four socket cap screw, Dismantle the fitting .</li> <li>Dig a hole 95mm wide and 105mm deep to accommodate the ground tube.</li> <li>Line the bottom with fine shingle to allow for drainage and leveling of the fitting.</li> <li>Wire installation or replace needs an electric engineer or monitor by an electric engineer.</li> <li>Ensure the ground tube is flush with the surrounding ground and fill the space between the ground tube and the side of the hole flush with concrete.</li> <li>unscrew the gland nut to allow the mains supply cable to feed through</li> <li>Feed the mains cable through the gland nut allowing enough cable to connect to the terminal block on the lampholder assembly.</li> <li>Tighten the gland nut and lower the casing into the ground tube.</li> </ol>		Chip Brand	Brigelux
		Driver Brand	Done
		Color Temperature	3000K/6000K
		CRI	>70
		Input Voltage	12V AC/DC
		Lens Angle	90 degree
		P-RATING	IP67
		Electricity-Proof Grade	CLASS 1
		Lamp Power	3W
		Lamp Efficacy	180-200LM
Power Ractor	>0.5		