


ELS



APPLICATION

The ELS is compact size LED strip with field adjustable wattage and color temperature. An Ideal for a size restricted architectural applications as well as for storage areas, displays, institutions, industrial and retail applications.

FEATURES:

- Die-formed steel channel with knock-outs for versatile configuration and simple mounting.
- One continuous lens for 8-foot fixtures.
- All Steel surfaces are painted after fabrication with high gloss baked white matte powder paint.
- Frosted lens.
- Field adjustable wattage and color temperature.

MOUNTING:

- Fixture is wall or surface mounted or pendant mounted, or suspended mounted with chains. (V-hook and chain kit is ordered separately)
- Compatible with most ceiling types.

LED:

- High quality array LEDs.
- Color Rendering Index: > 80
- Field adjustable color temperature: 3500/4000/5000(K)
- Field adjustable wattage.

ELECTRICAL:

- High power factor electronic driver, operate from a 120 ~ 277 Vac input range.
- Features included over surge protection.
- Power Factor: typical > 0.90, THD <20.
- Dimming Control: 0-10V 10%~100%.
- <ELCU-200>
- Guarantees emergency lighting remains ON or is turned on when power to the control device is lost.
- Interfaces with fire alarm panel or security system.
- "Watchdog" feature allows emergency loads to be controlled in tandem with normal power loads.
- UL listed for use in emergency circuits.

LISTING:

- UL/CUL listed and labeled.
- DLC listed.
- Suitable for dry and damp locations.
- CEC Compliant EM (please contact for more information)
- 5 years warranty.

CONFIGURATIONS

	Size	LED Watts	Lumen Output	Color Temp.	Lumen Efficiency
ELS	4FT	18W, 25W, 30W	2340lm, 3250lm, 3900lm	4000K	130 lm/W
		34W, 38W, 45W	4550lm, 5200lm, 5850lm		
	8FT	38W, 46W, 54W	4940lm, 5980lm, 7020lm		
		65W, 75W, 90W	8450lm, 9750lm, 11700lm		

: Based on 4000K.

ORDERING INFORMATION

EXAMPLE: ELS-4-L30/25/18-35/40/50K-UNV


MODEL	LENGTH		LED		COLOR TEMP.		VOLTAGE		MOUNTING	
ELS	4	4' Length	L30/25/18 L45/38/34	18W /25W /30W LED 34W /38W /45W LED	-35/40/50K	Selectable 35/40/50K	UNV	120-277V	(Blank) VH TB	Surface Mount V-Hook T-bar Clip Mounting
	8	8' Length	L54/46/38 L90/75/65	38W /46W /54W LED 65W /75W /90W LED						

PRESET		OPTIONS	
(Blank) PS	Non-Preset Preset Request *Factory default setting: 4-L25-40K 4-L38-40K 8-L54-40K 8-L75-40K	EMG5 EMG8 EMG16 ELCU-200 WG AMB	5W EM Battery Backup (CEC Compliant EM) ¹ 8W EM Battery Backup (CEC Compliant EM) ¹ 16W EM Battery Backup (CEC Compliant EM) ¹ Fail-to-on Emergency lighting, UL924 ² Wire Guard Anti-Microbial Coating (Matte Skye White)

NOTES:

1. Contact factory for other emergency ballast options.
2. Shipped separately.

ELS



Specifications: 4FT


Length: 48 (1219)
 Width: 3-3/8 (85)
 Depth: 3-1/2 (90)

Specifications: 8FT

Length: 96 (2438)
 Width: 3-3/8 (85)
 Depth: 3-1/2 (90)

All dimensions are in inches (millimeters).

Mounting Options	Image	Ordering Code
V-hook for Chain Mount	<p>Chain is provided.</p>	VH
T-Bar Clip Mount		TB



Field selectable access on the side