WAC LIGHTING

WL-LED100TR

Step And Wall Light

Model & Voltage	Color Temp & CRI	Lumens	Finish
WL-LED100TR 120 VAC	Red 90	72	WT White on
	Blue 90	72	Aluminum
	Amber 90	72	
	3000K 90	72	
	2700K 90	72	

Example: WL-LED100TR-27-WT

FEATURES

- Can be painted to match the color of the surface
- Low profile, flush to wall aesthetics with no visible hardware
- Balanced lighting, free of shadows with minimum glare
- Up to 200 fixtures can be connected in parallel
- 5 year warranty

SPECIFICATIONS

Construction Die-cast corrosion resistant aluminum alloy

Power: 3.3W

Input: 120 VAC,50/60Hz
Dimming: ELV: 100-10%
Light Source: Integrated LED
Rated Life: 50,000 Hours

Mounting: Fits into 2" x 4" J-Box with minimum inside dimensions of 3"L x

2"W x 2"D

Finish: Enamel Coated White on Aluminum

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Damp Location Listed, ADA, Title 24 JA8 Compliant

REPLACEMENT PARTS

RM-1X4-30-100TR - 120V Timeless Rpl Module



FINISHES:

Fixture Type:

Project:

Location:

Catalog Number:



Aluminum

LINE DRAWING

