

WAC LIGHTING

WL-LED200TR

Step And Wall Light

Model & Voltage	Color Temp & CRI	Lumens	Finish
WL-LED200TR 120 VAC	Red 90 Blue 90 Amber 90 3000K 90 2700K 90	72 72 72 72 72	WT White on Aluminum

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **WL-LED200TR-27-WT**

FEATURES


- Can be painted to match the color of the surface
- Low profile, flush to wall aesthetics with no visible hardware
- Balanced lighting, free of shadows with minimum glare
- Up to 200 fixtures can be connected in parallel
- 5 year warranty

SPECIFICATIONS

Construction	Die-cast corrosion resistant aluminum alloy
Power:	3.3W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Integrated LED
Rated Life:	50,000 Hours
Mounting:	Fits into 2" x 4" J-Box with minimum inside dimensions of 3"L x 2"W x 2"D
Finish:	Enamel Coated White on Aluminum
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Damp Location Listed, ADA, Title 24 JA8 Compliant

REPLACEMENT PARTS

RM-1X4-30-200TR - 120V Replacement Module



FINISHES:



White on Aluminum

LINE DRAWING

